

# Specifications

**BTUH** .....D-30 -Hi 30,000  
 Lo 19,900  
 D-40 -Hi 40,000  
 Lo 6,500

**Efficiency** ....Thermal up to 86.4%

**Gas Supply** .....Natural or LP

**Pilot System** .....Piezo Spark

**Safety Controls** .....ANSI/AGA  
 Certified

**Safety Tested** ....Warnock Hersey  
 to CGA/AGA/ANSI Std.

**Shipping Weight** ...D-30 -175 lbs.  
 D-40 -200 lbs.

Products, specifications, and prices  
 subject to change without notice

Consult our Owners Manual for all final dimensions.  
 Menota products are manufactured in the U.S.A.



## Standard Equipment

Log set, log rack, coal bed, D-30:  
 2-level burner, D-40: 3-level  
 burner, 2 blowers with rheostat,  
 neo-ceram glass and firebrick.

## Options

Black, black onyx, vintage iron,  
 cast, copper, nickel, silver, brass,  
 and 24k gold fronts; wall switch,  
 remote control and thermostat.

Rectangular or arched surround.  
 Brass or black surround trim.

Custom surrounds available upon  
 request. Co-linear or co-axial flue  
 venting. Natural vent (B-Vent),  
 D-30 only.

	D-30 TimberFire			D-40 Deep Timber		
<b>A</b>	24"	27"	31"	31"	33"	36"
<b>B</b>	36"	40"	44"	44"	48"	52"
<b>C</b>	30 7/16"			*34 7/8" **34"		
<b>D</b>	22 1/4"			24 1/4"		
<b>E</b>	16 3/8"			16 13/16"		
<b>F</b>	1 1/8"			1 1/8"		
<b>G</b>	19"			23"		
<b>H</b>	30 7/16"			36 1/2"		
<b>I</b>	15 1/2"			19 1/8"		
<b>J</b>	8 3/8"			9"		

\*With no Surround Trim or with the Standard Surround Trim C=34 7/8".

\*\*With the Optional Deeper Surround Trim C=33 3/4"

## D-30 Andover Arched Faceplate

L-24 7/8" M-40 1/4" N-28 7/8" RADIUS-52 11/32"

## D-30 Bentley Arched Faceplate

L-28 7/8" M-40 1/4" N-22 7/8" RADIUS-36 7/8"

## D-40 Andover & Bentley Arched Faceplate

L-28 3/8" M-44 3/16" N-33 3/8" RADIUS-51 1/2"

